

USB To RS-232/422/485 (4 ports) Converter US-401-I



- USB
 - ◇ Chipset : FTDI FT4232
 - ◇ Compliant : USB 1.0 , 1.1 , 2.0
 - ◇ Connector : USB type B
 - ◇ USB 2.0 High Speed (480M bps)
 - ◇ Baud Rates : Full speed 12 Mbps
- Serial Port
 - ◇ Port : RS-232/422/485 * 4 Ports (Auto Detect)
 - ◇ RS-232 : TXD , RXD , RTS , CTS , DTR , DSR , DCD
 - ◇ RS-422 : RxD+ , RxD- , TxD+ , TxD- ,
 - ◇ RS-485 : Data+ , Data-
 - ◇ RS-232 ,RS-422 , RS-485 Auto Detect(3 Selection 1)
 - ◇ RS-422 , RS-485 Surge Protect
 - ◇ Receive buffer : 2K Byte
 - ◇ Transmit buffer: 2K Byte
 - ◇ Transmit / Receive (Signal 3000V DC optical isolation protect)
 - ◇ 3000V DC to DC isolation protect (For RS232/422/485)
 - ◇ Baud Rate : 300 ~ 230.4 K bps
 - ◇ Flow Control : X-On / X-Off or Hardware
 - ◇ Pull high / Low: 1K/1K Ohm
- Driver Support (Virtual Com Utility)
 - ◇ Windows - 2000 / Server 2003 / XP / XP 64 bit / Vista / Windows 7
 - ◇ Mac osx / Linux 2.4 / 2.6
- Power :DC-JACK (9V~24V) / USB POWER
- Dimension
 - ◇ Size :110* 170 * 33 mm (W * D * H)
 - ◇ Weight :500 gm
- Environment
 - ◇ Operating Temp : 0~70□
 - ◇ Storage Temp : -40 to 85□
 - ◇ Humidity : 5~95 % RH

